




# Information Modification & New addition

## ⊕ 121P-50,-70,-100 PH Bit



◆ DIN3126 Form E6.3




121P (PH)	R (mm)	L=50 (g)	L=70 (g)	L=100 (g)	(pcs.)
New 1	4.5	12	15	23	10
New 2	5.5	12	15	23	10
New 3	---	13	16	24	10

## ⊙ 121H-50,-70,-100-150 HEX Bit



◆ DIN3126 Form E6.3




121H (mm)	R (mm)	L=50 (g)	L=70 (g)	L=100 (g)	(pcs.)
3	4.0	12	15	37	10
4	4.5	12	15	37	10
5	5.6	13	16	38	10
6	---	14	18	39	10

121H-150 (mm)	R (mm)	L (mm)	(g)	(pcs.)
3	4.5	150	37	10
4	5.0	150	37	10
5	6.0	150	38	10
6	---	150	39	10

## ⊙ 121T-50,-70,-100,-150 TORX® Bit



◆ DIN3126 Form E6.3




121T (T)	R (mm)	L=50 (g)	L=70 (g)	L=100 (g)	(pcs.)
T20	4.1	12	16	24	10
T25	4.6	12	16	24	10
T27	5.2	13	17	24	10
T30	5.7	13	17	25	10
T40	---	14	18	26	10

121T-150 (T)	R (mm)	L (mm)	(g)	(pcs.)
T20	4.5	150	37	10
T25	5.0	150	37	10
T27	5.6	150	37	10
T30	6.0	150	38	10
T40	---	150	39	10

## ⊙ 121T-70 TORX® Bit (Tamper-Resistant)




◆ DIN3126 Form E6.3



121T (TH)	R (mm)	L=70 (g)	(g)	(pcs.)
T20H	4.1	16		10
T25H	4.6	16		10
T27H	5.2	17		10
T30H	5.7	17		10
T40H	---	18		10

## ⊙ 12137E 1/4" Impact Bit Holder



	□	D <sub>1</sub> (mm)	D <sub>2</sub> (mm)	L (mm)	(g)	(pcs.)	⊙
New 12137E	1/4"	12	13	40	22	10	1201A 1201B
13137E	3/8"	12	19	40	40	10	1301C
14137E	1/2"	12	25	48	70	10	1401C
13142-F6.3	3/8"	16.5	19	45	60	10	1301C
14142-F6.3	1/2"	16.5	25	45	100	10	1401C

12137E, 13137E and 14147E can be used with various 1/4" bits, DIN 3126-C6.3, E6.3 and Double ended type.

## ⊙ 13142-F6.3 3/8" Impact Bit Holder

## ⊙ 14142-F6.3 1/2" Quick Release type

◇ DIN3126 Form F6.3

